

# CI-625T

Ref: LDACI625TS01

The CI-625 is a high performance column speaker for professional installations.

Its stylized design allows to adapt it to all the environments in addition to IP protection. The CI-625 can be installed on wall or columns. For that reason, it has a bracket which allows to install the acoustic box in vertical or horizontal position and rotate it 180° around itself.

The 6 drivers of 2.5", contained inside of it, give to any installation a high fidelity of sound by means of the adaptable acoustic design.



### CI-625T features:

- High sensitivity: 92 dB (1 W, 1 m)
- High quality audio for music or voice
- Low loss transformer for 70/100V PA lines
- Easy to install
- Metallic grille acoustically transparent

### Technical specifications:

| Model                               | CI-625T  |
|-------------------------------------|--|
| <b>Reference</b>                    | <b>LDACI625TS01</b>  |
| Nominal power                       | 30 W RMS   |
| Frequency response                  | 170 Hz- 15 kHz   |
| Sensitivity                         | 92 dB +/- 3 dB (1W, 1m)                                      |
| Material                            | Al (body)<br>Fe (grille)                                     |
| Colour                              | White, RAL 9016  |
| IP protection grade                 | IP55   |
| Connector                           | N/A. 3-wire cable with feedthrough                           |
| Fixing                              | Wall-mount with 2 metal brackets. Adjustable angle up to 15° |
| Transformer (70/100 V)              | 30/15 W @100 V<br>15/7.5 W @70 V                             |
| Dimensions (height x width x depth) | 548 x 106 x 75 mm  |
| Weight                              | 2.74 kg  |