

CI-625T

Ref: LDACI625TS01

The CI-625 is a high performance column speaker for professional installations.

Its stylized design allows to adapt it to all the environments in addition to IP protection. The CI-625 can be installed on wall or columns. For that reason, it has a bracket which allows to install the acoustic box in vertical or horizontal position and rotate it 180° around itself.

The 6 drivers of 2.5", contained inside of it, give to any installation a high fidelity of sound by means of the adaptable acoustic design.



CI-625T features:

- High sensitivity: 92 dB (1 W, 1 m)
- High quality audio for music or voice
- Low loss transformer for 70/100V PA lines
- Easy to install
- Metallic grille acoustically transparent

Technical specifications:

Model	CI-625T
Reference	LDACI625TS01
Nominal power	30 W RMS
Frequency response	170 Hz- 15 kHz
Sensitivity	92 dB +/- 3 dB (1W, 1m)
Material	Al (body) Fe (grille)
Colour	White, RAL 9016
IP protection grade	IP55
Connector	N/A. 3-wire cable with feedthrough
Fixing	Wall-mount with 2 metal brackets. Adjustable angle up to 15°
Transformer (70/100 V)	30/15 W @100 V 15/7.5 W @70 V
Dimensions (height x width x depth)	548 x 106 x 75 mm
Weight	2.74 kg