

CS-42T

Ref: LDACS42TS01

The CS-42T is a ceiling speaker with high sensitivity. The enclosure and the grille are both made of metal. It provides an easy installation with a 34 contacts barrier strip connector. Thanks to its integrated impedance transformer, it is possible to install it in 70/100 V PA lines choosing the power configuration most suited to the needs of the venue.

The installation is very quick and flexible thanks to the metal clamps, which allow to install the speaker both into metallic sheet tile and plaster ceilings.

Features CS-42T:

- High performance: 92 dB (1 W, 1 m)
- Excellent quality of music and voice playback
- Low lost transformer for 70/100 V PA lines
- Easy to install
- Metallic grille acoustically transparent



Technical specifications:

| Model | CS-42T |
|-------------------------------|---|
| Reference | LDACS42TS01 |
| Nominal power | 6 W RMS |
| Frequency response | 100Hz- 18 kHz +/- 5dB |
| Sensitivity | 92 dB +/- 3 dB (1W, 1m) |
| Material | Iron (body and grille) |
| Colour | White, RAL 9016 |
| Connector | Barrier strip type |
| Fixing | Installation by metallic clamps for metallic sheet tile and plaster ceilings. |
| Transformer (70/100 V) | 6 W or 3 W @100 V 3 W or 1,5 W @70 V |
| Dimensions (diameter x depth) | 200 x 65 mm |
| Drill hole for mounting | 185 mm |
| Weight | 0,8 kg |