Applus

Constancy of Performance Certificate

LGAI Technological Center S.A. (APPLUS), Notified Body No. 0370, issues this certificate to:

APPLICANT

Placed on the market under the name of

LDA audioTech S.L.

C/ Severo Ochoa, 31 – Parque Tecnológico Andalucía 25590 Málaga (España)

Manufactured in production plant:

25/32305163

PRODUCT

Fire detection and fire alarm systems. Components of voice alarm systems. Loudspeakers

Model: VTX-15TN (LDAVTX15TNS01), VTX-60TN (LDAVTX60TNS01), VTX-90TN (LDAVTX90TNS01)

APPLICABLE REGULATION

Construction Product Regulation (CPR)

In compliance with Regulation (EU) No. 305/2011 of the European Parliament and of the Council of 9 March 2011

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex 7A of the standard:

EN 54-24:2008

Under **system 1** for the performance set out in this certificate are applied and the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

No. 0370-CPR-6611

Date issued: 15/09/2025 First issue date: 30/06/2023 Follow-up date: before 31/07/2026

The validity of this certificate remains valid as long as the harmonised standard, the construction product, the EVCP methods and the manufacturing conditions at the plant are not significantly modified, unless suspended or withdrawn by the notified product certification body.

This document is not valid without its technical annex; whose number coincides with that of the certificate.



Xavier Ruiz Peña Managing Director Conformity Assessment



LGAI Technological Center S.A. (APPLUS)
Notified Body No. 0370
Compute LIAB, Bondo de la Font del Cormo de

Campus UAB. Ronda de la Font del Carme s/n 08193 Bellaterra, Barcelona (Spain)







LGAI Technological Center S.A. (APPLUS) Campus UAB. Ronda de la Font del Carme s/n 08193 Bellaterra, Barcelona (Spain) Technical annex Ed. 1 23/09/2025

0370-CPR-6611

Technical Annex

Annex according to EN 54-24:2008

Fire detection and fire alarm systems. Part 24: components of voice alarm systems. Loudspeakers

| Essential characteristics | Clauses in this European Standard | Mandated level(s) or class(es) |
|--|--------------------------------------|--------------------------------|
| Frequency response limits | 4.2 | PASS |
| Durability | 4.3 | PASS |
| Construction | 4.4 | PASS Type B |
| Marking and data | 4.5 | PASS |
| Reproducibility | 5.2 | PASS |
| Rated impedance | 5.3 | PASS |
| Horizontal and vertical coverage angles | 5.4 | PASS |
| Maximum sound pressure level | 5.5 | PASS |
| Rated noise power (durability) | 5.6 | PASS |
| Dry heat (operational) | 5.7 | PASS |
| Dry heat (endurance) | 5.8 | PASS |
| Cold (operational) | 5.9 | PASS |
| Damp heat, cyclic (operational) | 5.10 | PASS |
| Damp heat, steady state (endurance) | 5.11 | PASS |
| Damp heat, cyclic (endurance) | 5.12 | PASS |
| Sulfur dioxide (SO2) corrosion (endurance) | 5.13 | PASS |
| Shock (operational) | 5.14 | PASS |
| Impact (operational) | 5.15 | PASS |
| Vibration, sinusoidal (operational) | 5.16 | PASS |
| Vibration, sinusoidal (endurance) | 5.17 | PASS |
| Enclosure protection | 5.18 | PASS |

PASS; NPD = No Performance Determined, NA = Not Apply